

HomeSecurityVideoIntercomSystem



# MAIN FEATURES

- **Clear and Sharp Monitor**

Using High-Sensitivity 1/3" CCD Image Sensor Combined with the 4" CRT will produce sharp pictures and excellent resolution. Camera must be positioned to avoid direct sunlight.

- **Infrared Viewing for Night Time**

For clear viewing, the camera is equipped with infrared LED to assist viewing at night time. Additional light is highly recommended for night situation.

- **Available Sub-Monitor (Up to 4 Monitors)**

A supplementary monitor can be additionally installed. This can be a combination of standard or a Hands Free Monitor.

- **Long Distance Operating**

When correct, recommended cables are used, it can extend your range up to 150 metres. Even longer distances can be achieved, but it is essential to discuss your needs with authorised Videoman dealers.

- **Available Sub-Audio Handset**

Up to 2 Audio Handsets per Monitor.

- **Automatic and Manual Visitor Verification**

- **Multiple 2 Camera Set Up**

More than 1 door call stations are possible using our compact EAC-910 relay unit.

- **Intercommunication Between Monitors**

Internal Intercommunication between Monitors when more than 1 Monitor are installed.

- **Camera can be either Surface Mounted or Flush Mounted**

ABS Plastic Camera can be completely flush mounted using our Chrome or Brass Plates for that extra style and security.

- **Video Memory Module**

This high resolution video memory module can store up to 32 frames of still picture of your visitors automatically, even when you are not at home. Now you will always know who came to see you when you arrive back home.

- **Hands Free Operation**

Only available to VS-980 system.

# GENERAL SPECIFICATIONS

Monitor VS-901M		Monitor VS-901M	
Power source	DC15.5V	Power source	DC12V from monitor
Power consumption	13W(Max)	Camera Unit	1/3"B&W CCD 270,000 pixels
	2.4W(standby)		With infrared LEDs
CRT	4" CRT Direct view flat type	Camera Lens	F=3.6mm 92.5deg
Operation temperature	-10C(23F to 122F)	Minimum illumination	1 Lux
Cabbling	2 Strokes electronic chime	Object pick up range	Appx Hol.60deg Ver. 50deg
Communication	Simultaneous with handset	Resolution	380TV Line
Dimensions	185Wx220Hx55D mm	Dimensions	98Wx130Hx46D mm
Weight(approx)	1200g	Weight(approx)	220g

## OPTIONAL UNITS



VS-901M  
Extra Sub Monitor



SA-960A  
Sub Audio Handset



VS-932  
Video Memory 32 Frames



ST-160  
Electric Latch

• Also available VS-010 Multi Camera Relay, Brass or Chrome plate available for camera VS-900C

# VIDEOMAN

## Intercoms and CCTV Systems

FOR SALES AND SERVICE PLEASE CONTACT YOUR LOCAL DEALER

\*Features and specifications subject to change without notice.  
Website: [www.videoman.com.au](http://www.videoman.com.au)